

Page 1/10

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1 Product identifier · Trade name: FEYCOPUR HS Härter 85 langsam 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) · Product category PC9a Coatings and paints, thinners, paint removers · Application of the substance / the mixture Hardening agent/ Curing agent · 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: **FEYCOLOR GmbH** Maxhüttenstraße 6 93055 Regensburg Germany Tel.: +49 (0) 941-60497-0 Fax: +49 (0) 941-60497-30 info@feycolor.com www.feycolor.com Office hours: Monday - Thursday: 08:00 - 12:00 und 13:00 - 16:00 Friday: 08:00 - 12:00 Email: sd@feycolor.com www.feycolor.com · 1.4 Emergency telephone number: +49 (0) 700 24 11 21 12 (FCM) **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 flame Flam. Liq. 3 H226 Flammable liquid and vapour. Acute Tox. 4 H332 Harmful if inhaled. Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness. · 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. (Contd. on page 2)



Safety data sheet according to 1907/2006/EC, Article 31

Page 2/10

Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

Trade name: FEYCOPUR HS Härter 85 langsam

· Hazard pictog	(Contd. of page 1)
GHS02 GHS	07
· Signal word W	/arning
	nining components of labelling:
	e diisocyanate, oligomers
2-Butoxyethyl a	
n-Butyl acetate	ethylethyl acetate
· Hazard statem	
	mmable liquid and vapour.
H332 Ha	rmful if inhaled.
	y cause an allergic skin reaction.
	y cause respiratory irritation. May cause drowsiness or dizziness.
Precautionary	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P3	353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or
	shower].
P304+P340	
P312	Call a POISON CENTER/doctor if you feel unwell.
• Additional info	ins isocyanates. May produce an allergic reaction.
	ofessional users.
· 2.3 Other haza	
Results of PB	T and vPvB assessment
· PBT: Not applie	
· vPvB: Not app	licable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
	Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335, EUH204	50-100%
	2-Butoxyethyl acetate Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	10-25%
	2-Methoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	10-25%
	(Cont	d. on page 3)



Page 3/10

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

Trade name: FEYCOPUR HS Härter 85 langsam

	(Con	td. of page 2 <u>)</u>
CAS: 123-86-4 EINECS: 204-658-1	n-Butyl acetate	5-<10%
Reg.nr.: 01-2119485493-29 CAS: 822-06-0	hexamethylene-di-isocyanate	<0.1%
	Acute Tox. 2, H330; & Resp. Sens. 1, H334; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204	•
	Specific concentration limits: Resp. Sens. 1; H334: C \ge 0.5 % Skin Sens. 1; H317: C \ge 0.5 %	
· Additional information: Fo	r the wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

In case of irregular breathing or respiratory arrest provide artificial respiration.

• After inhalation: Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Alcohol resistant foam
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released: Nitrogen oxides (NOx) Carbon monoxide (CO) Hydrogen cyanide (HCN) **5.3 Advice for firefighters**

· Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- \cdot 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 4)

GB



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

Page 4/10

Trade name: FEYCOPUR HS Härter 85 langsam

(Contd. of page 3) Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. Contain and collect spillages with non-combustible absorbent materials (e.g. sand, earth, diatomaceous earth) and place in a suitable container. Decontaminate immediately with suitable mixture (flammable): - as such usable (inflammatory!): water 45 Vol.% ethanol or isopropanol 50 Vol.% ammonia solution (Density= 0.88) 5 Vol.% - alternatively (non-flammable): 5 Vol.% sodium carbonate 95 Vol.% water Add the same decontaminant to any residues and allow to stand for several days in an non-sealed container until no further reaction occurs. Once this stage is reached, close the container and dispose of in accordance with the waste regulations (see Section 13). 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. **SECTION 7: Handling and storage**

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Persons with a history of asthma, allergies or chronic or recurrent respiratory diseases should only be employed in processes in which this product is used under appropriate medical supervision.

• **Information about fire - and explosion protection:** Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- **Information about storage in one common storage facility:** Do not store together with reducing agents, heavy-metal compounds, acids and alkalis. Store away from foodstuffs.
- Further information about storage conditions:
 Keep container tightly sealed.
 Store separately from oxidising agents, strongly alkaline and strongly acidic materials, amines, alcohol and water.

· Storage class: 3

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

28182-81-2 Hexamethylene diisocyanate, oligomers

EBW Short-term value: 0.5 mg/m³

exposition evaluation valu TRGS 430 (EBW)

(Contd. on page 5)



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

Page 5/10

Trade name: FEYCOPUR HS Härter 85 langsam

112 0	Contd. of page 4
	Short-term value: 332 mg/m ³ , 50 ppm
	Long-term value: 133 mg/m³, 20 ppm Sk
108-6	5-6 2-Methoxy-1-methylethyl acetate
WEL	Short-term value: 548 mg/m ³ , 100 ppm
	Long-term value: 274 mg/m³, 50 ppm Sk
123-8	6-4 n-Butyl acetate
WEL	Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm
822-0	6-0 hexamethylene-di-isocyanate
WEL	Short-term value: 0.07 mg/m ³
	Long-term value: 0.02 mg/m³ Sen; as -NCO
	dients with biological limit values:
	6-0 hexamethylene-di-isocyanate
BMG	/ 1 µmol creatinine/mol Medium: urine
	Sampling time: At the end of the period od exposure
	Parameter: isocyanate-derived diamine
Addit	ional information: The lists valid during the making were used as basis.
	xposure controls
	opriate engineering controls No further data; see item 7.
	i dual protection measures, such as personal protective equipment ersonal protective equipment, including respiratory protecitve equipment, used to control exposure t
	dous substances must be selected to meet the requirements of the COSHH Regulations.
	ral protective and hygienic measures:
	diately remove all soiled and contaminated clothing
	hands before breaks and at the end of work.
	iratory protection:
	A/P2 (EN 141, EN 143)
	In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longe
	exposure use self-contained respiratory protective device.
Land	neotootion

· Hand protection



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves Butyl rubber, BR

Recommended thickness of the material: ≥ 0.7 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

(Contd. of page 5)

Trade name: FEYCOPUR HS Härter 85 langsam

· Breakthrough time of glove material

For the mixture of chemicals the penetration time has to be at least 60 minutes (Permeation according to EN 374 Part 3: Level 3).

· Eye/face protection

Tightly sealed goggles

SECTION 9: Physical and chemical propertie	S
• 9.1 Information on basic physical and chemical p	roperties
General Information	
· Physical state	Fluid
· Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
 Melting point/freezing point: 	Undetermined.
Boiling point or initial boiling point and boiling	
range	124-128 °C (123-86-4 n-Butyl acetate)
· Flammability	Flammable.
Lower and upper explosion limit	
· Lower:	1.5 Vol % (108-65-6 2-Methoxy-1-methylethyl acetate)
· Upper:	10.8 Vol % (108-65-6 2-Methoxy-1-methylethyl acetate)
Flash point:	30 °C (DIN 53213)
Ignition temperature:	280 °C (DIN 51794, 112-07-2 2-Butoxyethyl acetate)
Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	
Kinematic viscosity at 20 °C	13 s (DIN 53211/4)
· Dynamic:	Not determined.
· Solubility	
· water:	Not miscible or difficult to mix.
 Partition coefficient n-octanol/water (log value) 	Not determined.
· Vapour pressure at 20 °C:	10.7 hPa (123-86-4 n-Butyl acetate)
Density and/or relative density	
· Density at 20 °C:	1.05 g/cm³ (DIN 53217)
· Relative density	Not determined.
· Vapour density	Not determined.
• 9.2 Other information	
· Appearance:	
· Form:	Fluid
· Important information on protection of health an	
environment, and on safety.	ŭ
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive
	air/vapour mixtures are possible.
· Solvent content:	
· VOC (EC)	45.90 %
	(Contd. on page 7)

Page 6/10



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

Page 7/10

Trade name: FEYCOPUR HS Härter 85 langsam

Solido contont (weight %):	E4 1 0/	(Contd. of page
Solids content (weight-%): Change in condition	54.1 %	
Evaporation rate	Not determined.	
Information with regard to physical hazard c	lasses	
Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Flammable liquid and vapour.	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flamm	able	
gases in contact with water	Void	
Öxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- **10.6 Hazardous decomposition products:** Possible in traces. Nitrogen oxides Hydrogen chloride (HCl) Hydrogen cyanide (prussic acid)

Carbon monoxide Nitrogen oxides (NOx)

SECTION 11: Toxicological information

• 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 • Acute toxicity Harmful if inhaled.

· LD/LC50 values relevant for classification:

28182-81-2 Hexamethylene diisocyanate, oligomers

Inhalative LC50/4 h 1.5 mg/l (rat)

• Respiratory or skin sensitisation May cause an allergic skin reaction.

• STOT-single exposure May cause respiratory irritation. May cause drowsiness or dizziness.

(Contd. on page 8)



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

Trade name: FEYCOPUR HS Härter 85 langsam

· 11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) : slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number ADR, IMDG, IATA	UN1263	
	011205	
14.2 UN proper shipping name		
ADR	UN1263 PAINT RELATED MATERIAL	
IMDG, IATA	PAINT RELATED MATERIAL	
14.3 Transport hazard class(es) ADR		
Class	3 (F1) Flammable liquids.	

(Contd. of page 7)



Page 9/10

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

Trade name: FEYCOPUR HS Härter 85 langsam

	(Contd. of page 8)
· Label	3
· IMDG, IATA	
· Class	3 Flammable liquids.
Label	3
 14.4 Packing group ADR, IMDG, IATA 	III
 14.5 Environmental hazards: Marine pollutant: 	No
 14.6 Special precautions for user 	Warning: Flammable liquids.
Hazard identification number (Kemler code):	30
 EMS Number: Stowage Category 	F-E, <u>S-E</u> A
 14.7 Maritime transport in bulk according to IM instruments 	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
Transport category	3
Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
· UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

• Seveso category P5c FLAMMABLE LIQUIDS

· Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· National regulations:

Additional classification according to Decree on Hazardous Materials, Annex II:

ClassShare in %NK25-50

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 10)



Page 10/10

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

(Contd. of page 9)

Trade name: FEYCOPUR HS Härter 85 langsam

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- Flammable liquid and vapour. H226
- Harmful if swallowed. H302
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH204 Contains isocyanates. May produce an allergic reaction.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008. Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Lig. 3: Flammable liquids - Category 3

Acute Tox. 2: Acute toxicity – Category 2 Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

** Data compared to the previous version altered.