

Page 1/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 26 (replaces version 25)

Revision: 01.02.2023

SECTION 1: Id	dentification of the substance/mixture and of the company/undertaking
· 1.1 Product ide	entifier
• 1.2 Relevant ide No further releva	EYCOTECT 220 1K Kunststoffprimer entified uses of the substance or mixture and uses advised against ant information available. the substance / the mixture Priming
 1.3 Details of the Manufacturer/S FEYCOLOR Gm Maxhüttenstraße 93055 Regensbu Germany 	nbH e 6
Tel.: +49 (0) 941 Fax: +49 (0) 941 info@feycolor.co	
Office hours: Monday - Thurso Friday: 08:00 - 1	day: 08:00 - 12:00 und 13:00 - 16:00 12:00
Email: sd@feyco www.feycolor.co · 1.4 Emergency	
SECTION 2: H	lazards identification
· 2.1 Classification	on of the substance or mixture
· Classification a	according to Regulation (EC) No 1272/2008
flame	
Flam. Liq. 2	H225 Highly flammable liquid and vapour.
	hazard
STOT RE 2 Asp. Tox. 1	H373 May cause damage to organs through prolonged or repeated exposure.H304 May be fatal if swallowed and enters airways.
<!-- -->	
Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2	H319 Causes serious eye irritation.
STOT SE 3	H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.
Aquatic Chronic	3 H412 Harmful to aquatic life with long lasting effects.
	ents rding to Regulation (EC) No 1272/2008 classified and labelled according to the GB CLP regulation. (Contd. on page



Page 2/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 26 (replaces version 25)

Revision: 01.02.2023

Trade name: FEYCOTECT 220 1K Kunststoffprimer

Hazard pictog	rams (Contd. of page
<u>< () > ()</u>	
GHS02 GHS	07 GHS08
Signal word D	anger
Hazard-determ	nining components of labelling:
Xylene	inning compenents of labeling.
Ethyl acetate	
	a (petroleum), light arom.
Ethylbenzene	
Hazard statem	ents
	hly flammable liquid and vapour.
	uses skin irritation.
	uses serious eye irritation.
	y cause respiratory irritation. May cause drowsiness or dizziness.
	y cause damage to organs through prolonged or repeated exposure.
	y be fatal if swallowed and enters airways.
H412 Ha	rmful to aquatic life with long lasting effects.
Precautionary	statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P321	Specific treatment (see on this label).
P331	Do NOT induce vomiting.
P303+P361+P3	353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water shower].
P305+P351+P3	338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses present and easy to do. Continue rinsing.
P362+P364	Take off contaminated clothing and wash it before reuse.
P501	Dispose of contents/container in accordance with local/regional/national/internation regulations.
2.3 Other haza	
	Γ and vPvB assessment
PBT: Not applie	
uppin	

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3) GB



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 26 (replaces version 25)

Revision: 01.02.2023

Page 3/10

Trade name: FEYCOTECT 220 1K Kunststoffprimer

	(Co	ntd. of page 2
Dangerous components:		
CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46	Ethyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	25-50%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	25-50%
CAS: 64742-95-6 EINECS: 265-199-0	Solvent naphtha (petroleum), light arom. 🚸 Flam. Liq. 3, H226; 🚸 Asp. Tox. 1, H304	2.5-<10%
CAS: 123-42-2 EINECS: 204-626-7 Reg.nr.: 01-2119473975-21	4-hydroxy-4-methylpentan-2-one ♦ Flam. Liq. 3, H226; ♦ Eye Irrit. 2, H319; STOT SE 3, H335 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 10 %	2.5-<10%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35	Ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412	2.5-<10%
CAS: 95-63-6 EINECS: 202-436-9	1,2,4-trimethylbenzene Flam. Liq. 3, H226; Aquatic Chronic 2, H411; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	2.5-<10%

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information: Immediately remove any clothing soiled by the product.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Seek immediate medical advice.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

(Contd. on page 4)

GB



Page 4/10

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 26 (replaces version 25)

Revision: 01.02.2023

(Contd. of page 3)

Trade name: FEYCOTECT 220 1K Kunststoffprimer

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away. · 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water. · 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. · 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. **SECTION 7: Handling and storage** · 7.1 Precautions for safe handling
 - Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that req	uire monitoring at the workplace:

141-78-6 Ethyl acetate

WEL Short-term value: 1468 mg/m³, 400 ppm Long-term value: 734 mg/m³, 200 ppm

1330-20-7 Xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV

(Contd. on page 5)

⁻ G



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 26 (replaces version 25)

Revision: 01.02.2023

(Contd. of page 4)

Page 5/10

Trade name: FEYCOTECT 220 1K Kunststoffprimer

123-42-2 4-hydroxy-4-methylpe	ntan-2-one

WEL Short-term value: 362 mg/m³, 75 ppm Long-term value: 241 mg/m³, 50 ppm

100-41-4 Ethylbenzene

WEL Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk

95-63-6 1,2,4-trimethylbenzene

WEL Long-term value: 125 mg/m³, 25 ppm ILV

· Ingredients with biological limit values:

1330-20-7 Xylene

BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes. Avoid contact with the eyes and skin.

Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

• Hand protection

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

GB



Safety data sheet according to 1907/2006/EC, Article 31


Printing date 01.02.2023

Version number 26 (replaces version 25)

Revision: 01.02.2023

(Contd. of page 5)

Trade name: FEYCOTECT 220 1K Kunststoffprimer



Tightly sealed goggles

SECTION 9: Physical and chemical properties		
• 9.1 Information on basic physical and chemical p	roperties	
General Information		
· Physical state	Fluid	
· Colour:	According to product specification	
· Odour:	Characteristic	
· Odour threshold:	Not determined.	
· Melting point/freezing point:	Undetermined.	
Boiling point or initial boiling point and boiling		
range	77-78 °C (141-78-6 Ethyl acetate)	
· Flammability	Highly flammable.	
· Lower and upper explosion limit		
· Lower:	1.1 Vol % (1330-20-7 Xylene)	
· Upper:	11.5 Vol % (141-78-6 Ethyl acetate)	
· Flash point:	10 °C (DIN 53213)	
Ignition temperature:	430 °C (DIN 51794, 100-41-4 Ethylbenzene)	
· Decomposition temperature:	Not determined.	
·pH	Not determined.	
· Viscosity:		
· Kinematic viscosity at 20 °C	13 s (DIN 53211/4)	
· Dynamic:	Not determined.	
· Solubility		
· water:	Not miscible or difficult to mix.	
· Partition coefficient n-octanol/water (log value)	Not determined.	
· Vapour pressure at 20 °C:	97 hPa (141-78-6 Ethyl acetate)	
· Density and/or relative density		
· Density at 20 °C:	0.912 g/cm³ (DIN 53217)	
· Relative density	Not determined.	
· Vapour density	Not determined.	
9.2 Other information		
· Appearance:		
· Form:	Fluid	
· Important information on protection of health an		
environment, and on safety.	u	
· Auto-ignition temperature:	Product is not selfigniting.	
· Explosive properties:	Product is not explosive. However, formation of explosive	
	air/vapour mixtures are possible.	
· Solvent content:		
· VOC (EC)	95.69 %	
· Solids content (weight-%):	4.2 %	
	(Contd. on page 7	



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 26 (replaces version 25)

Revision: 01.02.2023

Trade name: FEYCOTECT 220 1K Kunststoffprimer

		(Contd. of page
Change in condition		
Evaporation rate	Not determined.	
Information with regard to physical hazard clas	Ses	
Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Highly flammable liquid and vapour.	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flammable	le	
gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

1330-20-7 Xylene			
Oral	LD50	5,251 mg/kg (rat)	
	LD50	5,251 mg/kg (rat) >5,000 mg/kg (rabbit)	
Inhalative	LC50/4 h	29 mg/l (rat)	

Skin corrosion/irritation Causes skin irritation.

· Serious eye damage/irritation Causes serious eye irritation.

• STOT-single exposure May cause respiratory irritation. May cause drowsiness or dizziness.

• **STOT-repeated exposure** May cause damage to organs through prolonged or repeated exposure.

• Aspiration hazard May be fatal if swallowed and enters airways.

(Contd. on page 8)

GB



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 26 (replaces version 25)

Revision: 01.02.2023

(Contd. of page 7)

Trade name: FEYCOTECT 220 1K Kunststoffprimer

· 11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) : hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Harmful to aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

· 14.1 UN number or ID number		
· ADR, IMDG, IATA	UN1263	
14.2 UN proper shipping name		
ADR	UN1263 PAINT	
· IMDG, IATA	PAINT	

Page 8/10



Page 9/10

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 26 (replaces version 25)

Revision: 01.02.2023

Trade name: FEYCOTECT 220 1K Kunststoffprimer

	(Contd. of page
· 14.3 Transport hazard class(es)	
ADR	
3	
Class	3 (F1) Flammable liquids.
Label	3
· IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
· ADR, IMDG, IATA	ll
· 14.5 Environmental hazards:	
· Marine pollutant:	No
 14.6 Special precautions for user 	Warning: Flammable liquids.
Hazard identification number (Kemler code):	33
· EMS Number: · Stowage Category	F-E, <u>S-E</u> B
 14.7 Maritime transport in bulk according to IM instruments 	Not applicable.
· Transport/Additional information:	
 ADR Limited quantities (LQ) 	5L
· Transport category	5L 2
· Tunnel restriction code	D/E
·IMDG	
Limited quantities (LQ)	5L
· UN "Model Regulation":	UN 1263 PAINT, 3, II

SECTION 15: Regulatory information

 \cdot 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- \cdot Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements $5{,}000\ t$
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

(Contd. on page 10)

⁻ GB



Page 10/10

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 26 (replaces version 25)

Revision: 01.02.2023

Trade name: FEYCOTECT 220 1K Kunststoffprimer

· National regulations:

(Contd. of page 9)

· Additional classification according to Decree on Hazardous Materials, Annex II:

Class | Share in %

NK 50-100

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organisation ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO) ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.