

Page 1/10


Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.01.2023

Version number 178 (replaces version 177)

Revision: 10.01.2023





Page 2/10

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.01.2023

Version number 178 (replaces version 177)

Revision: 10.01.2023

Trade name: REDOCAR Universalspachtel

Hazard pictogr	rams (Contd. of page
<u><<>></u>	
GHS02 GHS	J7 GHS08
Signal word Da	anger
Hazard-determ	ining components of labelling:
Styrene	
maleic anhydrid	
2,2'-(m-tolylimin	
	s of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](
methylphenyl)ar Hazard statem	
	ble liquid and vapour.
H315 Causes	
	serious eye irritation.
	ise an allergic skin reaction.
	ed of damaging the unborn child.
	damage to the hearing organs through prolonged or repeated exposure.
Precautionary	statements
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. I smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P3	353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water shower].
P305+P351+P3	338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, present and easy to do. Continue rinsing.
P403+P235	Store in a well-ventilated place. Keep cool.
2.3 Other haza	rds
Results of PB1	Γ and vPvB assessment
PBT: Not applic	
vPvB: Not appl	icable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:				
EINECS: 202-851-5 Reg.nr.: 01-2119457861-32	Styrene Flam. Liq. 3, H226; & Repr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	≥10-<15%		
		(Contd. on page 3)		



Page 3/10

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.01.2023

Version number 178 (replaces version 177)

Revision: 10.01.2023

Trade name: REDOCAR Universalspachtel

CAS: 91-99-6 EINECS: 202-114-8	2,2'-(m-tolylimino)diethanol ♦ STOT RE 2, H373; ♦ Eye Dam. 1, H318; ♦ Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1B, H317	(Contd. of page 2) ≥0.1-<1%	
EC number: 911-490-9	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]- Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥0.1-<1%	
CAS: 108-31-6 EINECS: 203-571-6 Reg.nr.: 01-2119472428-31	maleic anhydride	≥0.001-<0.1%	
· Additional information: Fo	• Additional information: For the wording of the listed hazard phrases refer to section 16.		

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

• After skin contact: Immediately rinse with water.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- **5.2 Special hazards arising from the substance or mixture** During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.
- **SECTION 6: Accidental release measures**
- 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.

(Contd. on page 4)

GB



according to 1907/2006/EC, Article 31

Printing date 10.01.2023

Version number 178 (replaces version 177)

Revision: 10.01.2023

Trade name: REDOCAR Universalspachtel

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.

 Information about fire - and explosion protection: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.

• 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles: No special requirements.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.

· Storage class: 3

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:		
100-42-5 Styrene		
WEL Short-term value: 1080 mg/m³, 250 ppm Long-term value: 430 mg/m³, 100 ppm		
108-31-6 maleic anhydride		
WEL Short-term value: 3 mg/m³ Long-term value: 1 mg/m³ Sen		
 Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Appropriate engineering controls No further data; see item 7. Individual protection measures, such as personal protective equipment General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes. Avoid contact with the eyes and skin. 	(Contd. on page 5)	

(Contd. of page 3)

GB

Page 4/10



according to 1907/2006/EC, Article 31

Printing date 10.01.2023

Version number 178 (replaces version 177)

Revision: 10.01.2023

(Contd. of page 4)

GB

Trade name: REDOCAR Universalspachtel

· Respiratory protection:

Filter A/P2 (EN 141, EN 143)



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Fluorocarbon rubber (Viton)

Recommended thickness of the material: ≥ 0.7 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Breakthrough time of glove material** Value for the permeation: Level ≤ 6

· Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and ch General Information	ennear properties	
Physical state	Fluid	
Colour:	Beige	
Odour:	Characteristic	
Odour threshold:	Not determined.	
Melting point/freezing point:	Undetermined.	
Boiling point or initial boiling point and I	poiling	
range	145.2 °C (100-42-5 Styrene)	
Flammability	Flammable.	
Lower and upper explosion limit		
Lower:	1.2 Vol % (100-42-5 Styrene)	
Upper:	8.9 Vol % (100-42-5 Styrene)	
Flash point:	34 °C (DIN 53213)	
Ignition temperature:	480 °C (DIN 51794, 100-42-5 Styrene)	
Decomposition temperature:	Not determined.	
pH	Not determined.	
Viscosity:		
Kinematic viscosity	Not determined.	
Dynamic at 20 °C:	70,000-80,000 mPas	



Page 6/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.01.2023

Version number 178 (replaces version 177)

Revision: 10.01.2023

Trade name: REDOCAR Universalspachtel

	(Contd. of page
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure at 20 °C:	6 hPa (100-42-5 Styrene)
Density and/or relative density	
Density at 20 °C:	1.81 g/cm³ (DIN 53217)
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Viscous
Important information on protection of health and	k de la constante de
environment, and on safety.	
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive
Oskuszt szutezt	air/vapour mixtures are possible.
Solvent content:	4 00 %
VOC (EC)	1.03 %
Solids content (weight-%):	84.7 %
Change in condition	Net determine d
Evaporation rate	Not determined.
Information with regard to physical hazard classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable	
gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known.

• 10.4 Conditions to avoid No further relevant information available.

· 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 7)

⁻ GB



according to 1907/2006/EC, Article 31

Printing date 10.01.2023

Version number 178 (replaces version 177)

Trade name: REDOCAR Universalspachtel

10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Based on available data, the classification criteria are not met.
- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · Reproductive toxicity Suspected of damaging the unborn child.
- STOT-repeated exposure Causes damage to the hearing organs through prolonged or repeated exposure.
- · 11.2 Information on other hazards
- Endocrine disrupting properties
- 78-93-3 Methyl ethyl ketone

128-37-0 Butylated hydroxytoluene

SECTION 12: Ecological information

· 12.1 Toxicity

- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:
- Water hazard class 2 (German Regulation) : hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

UN3269

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

- · 14.1 UN number or ID number · ADR, IMDG, IATA

GB

Page 7/10

Revision: 10.01.2023

(Contd. of page 6)

List II

List II



Page 8/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.01.2023

Version number 178 (replaces version 177)

Revision: 10.01.2023

Trade name: REDOCAR Universalspachtel

	(Contd. of page 7
 14.2 UN proper shipping name ADR IMDG, IATA 	UN3269 POLYESTER RESIN KIT POLYESTER RESIN KIT
· 14.3 Transport hazard class(es)	
ADR	
· Class	3 (F3) Flammable liquids.
Label	3
· Class	3 Flammable liquids.
· Label	3
 14.4 Packing group ADR, IMDG, IATA 	III
 14.5 Environmental hazards: Marine pollutant: 	No
· 14.6 Special precautions for user	Warning: Flammable liquids.
 Hazard identification number (Kemler code): 	•
· EMS Number:	F-E,S-D
· Stowage Category	A
 14.7 Maritime transport in bulk according to IMC instruments) Not applicable.
 Transport/Additional information: 	
 ADR Limited quantities (LQ) Transport category Tunnel restriction code 	5L 3 E
 IMDG Limited quantities (LQ) 	5L
· UN "Model Regulation":	UN 3269 POLYESTER RESIN KIT, 3, III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

(Contd. on page 9) GB



according to 1907/2006/EC, Article 31

Printing date 10.01.2023

Version number 178 (replaces version 177)

Revision: 10.01.2023

(Contd. of page 8)

Trade name: REDOCAR Universalspachtel

Seveso category P5c FLAMMABLE LIQUIDS

• Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

National regulations:

· Additional classification according to Decree on Hazardous Materials, Annex II:

Class Share in %

NK 10-25

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- Flammable liquid and vapour. H226
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- Causes severe skin burns and eye damage. H314
- Causes skin irritation. H315
- May cause an allergic skin reaction. H317
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- May cause respiratory irritation. H335
- Suspected of damaging the unborn child. H361d
- H372 Causes damage to organs through prolonged or repeated exposure.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.
- EUH071 Corrosive to the respiratory tract.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids - Category 3

- Acute Tox. 4: Acute toxicity Category 4
- Skin Corr. 1B: Skin corrosion/irritation Category 1B Skin Irrit. 2: Skin corrosion/irritation Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Resp. Sens. 1: Respiratory sensitisation - Category 1

(Contd. on page 10)

GB

Page 9/10



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.01.2023

Version number 178 (replaces version 177)

Revision: 10.01.2023

Trade name: REDOCAR Universalspachtel

Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1A: Skin sensitisation – Category 1A Skin Sens. 1B: Skin sensitisation – Category 1B Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

* Data compared to the previous version altered.

(Contd. of page 9)

GB

Page 10/10